

**In the Specification**

Please amend paragraph [00017] as follows:

[00017] The house 2 will receive the brake mechanism 7 when the disc brake is assembled. In the bottom of the housing 2 there are two thorough openings for the thrust units as indicated above. Furthermore, the house 2 is furnished with a space for receiving the lever 18 of the brake mechanism 7. As illustrated in Figure 3, the house 2 also encloses the lever 18 of the brake mechanism. In other embodiments (not shown) the brake mechanism has only one thrust unit, in which case the house 2 will only have one opening in the bottom.

Please amend paragraph [00020] as follows:

[00020] Finally a cover 3 is provided to cover the opening of the house 2. The cover 3 is provided with a number of openings 14, to receive pull rods 4. Each pull rod 4 has a head 16 at one end and is threaded at the other end to receive nuts 5. Even though the pull rods 4 are shown with the heads 16 at the frame 1 and the threaded ends at the cover 3, a person skilled in the art realizes that the pull rods 4 may be inserted the other way around. Thus, the pull rods 4 may have the heads 16 at the cover 3. The pull rods 4 have a predetermined length. The length of the pull rods 4 is somewhat longer than the length of the house 2. As illustrated in Figure 2, the pull rods 4 clamp between the frame 1 and the cover 3 without passing through the house 2. The predetermined length is adapted to the wish to attain flexible pretension for the system of house 2, gasket 6, cover 3 and frame 1. In the shown embodiment there are six pull rods, but a person skilled in the art realizes that any number of pull rods 4 may be used as long as a sufficient fixation is established.